

**IN THE CLAIMS:**

Please amend claims 10 - 17 as follows:

10. (Amended) The system as claimed in claim [9] 8, wherein:

said input device selects a halftone to be used in printing the image data;

Al  
said storage device provides a plurality of calibrated tone-reproduction curves,  
each calibrated tone-reproduction curve corresponding to a distinct halftone type and  
media type combination;

said processor selects a calibrated tone-reproduction curve based on the  
selected media type and selected halftone type.

11. (Amended) The system as claimed in claim [9] 8, further comprising:

calibration means for performing a plurality of calibration operations, each  
calibration operation using a distinct media type;

said calibration means generating a tone-reproduction curve for each media  
type;

said storage device storing the generated the tone-reproduction curves and  
providing a plurality of stored calibrated tone-reproduction curves, each stored  
calibrated tone-reproduction curve corresponding to a distinct media type.

12. (Amended) The system as claimed in claim [9] 8, further comprising:

calibration means for performing a plurality of calibration operations, each  
calibration operation using a distinct media type;

said calibration means generating a tone-reproduction curve for each media type;

said input device selecting a halftone to be used in printing the image data;

Al  
said storage device storing the generated the tone-reproduction curves and providing a plurality of stored calibrated tone-reproduction curves, each stored calibrated tone-reproduction curve corresponding to a distinct halftone type and media type combination;

said processor selecting a calibrated tone-reproduction curve based on the selected media type and selected halftone type.

13. (Amended) The system as claimed in claim [9] 8, further comprising:  
calibration means for performing a plurality of calibration operations, each calibration operation using a distinct media type;

said calibration means generating a tone-reproduction curve for each media type calibration;

said calibration means comparing the plurality of tone-reproduction curves to group tone-reproduction curves having similar characteristics;

said calibration means selecting a single tone-reproduction curve from a group of tone-reproduction curves having similar characteristics, each single tone-reproduction curve being the tone-reproduction curve associated with the media types that generated the tone-reproduction curve having similar characteristics;

said storage device storing selected and non-grouped tone-reproduction curves;

said calibration means generating a map to link a stored tone-reproduction curve to a media type, a stored tone-reproduction curve being capable of being mapped to more than one media type;

said storage device providing a plurality of stored calibrated tone-reproduction curves, each stored calibrated tone-reproduction curve corresponding to a distinct media type.

14. (Amended) The system as claimed in claim [9] 8, further comprising:

calibration means for performing a plurality of calibration operations, each calibration operation using a distinct media type and halftone type combination;

said calibration means generating a tone-reproduction curve for each media type and halftone type combination calibration;

said calibration means comparing the plurality of tone-reproduction curves to group tone-reproduction curves having similar characteristics;

said calibration means selecting a single tone-reproduction curve from a group of tone-reproduction curves having similar characteristics, each single tone-reproduction curve being the tone-reproduction curve associated with the media type and halftone type combinations that generated the tone-reproduction curve having similar characteristics;

said storage device storing selected and non-grouped tone-reproduction curves;

said calibration means generating a map to link a stored tone-reproduction curve to a media type and halftone type combination, a stored tone-reproduction curve

Al

00750597-122200

being capable of being mapped to more than one media type and halftone type combination; and

said input device selecting a halftone to be used in printing the image data;

said storage device providing a plurality of stored calibrated tone-reproduction curves, each stored calibrated tone-reproduction curve corresponding to a distinct media type and halftone type combination;

said processor selecting a calibrated tone-reproduction curve based on the selected media type and selected halftone type.

15. (Amended) The system as claimed in claim [9] 8, further comprising:

an auto-segmentation circuit to determine a halftone to be used in printing the image data;

said storage device providing a plurality of calibrated tone-reproduction curves, each calibrated tone-reproduction curve corresponding to a distinct halftone type and media type combination;

said processor selecting a calibrated tone-reproduction curve based on the selected media type and determined halftone type.

16. (Amended) The system as claimed in claim [9] 8, further comprising:

calibration means for performing a plurality of calibration operations, each calibration operation using a distinct media type;

said calibration means generating a tone-reproduction curve for each media type; and

an auto-segmentation circuit to determine a halftone to be used in printing the image data;

AI  
said storage device storing the generated the tone-reproduction curves and providing a plurality of stored calibrated tone-reproduction curves, each stored calibrated tone-reproduction curve corresponding to a distinct halftone type and media type combination;

said processor selecting a calibrated tone-reproduction curve based on the selected media type and determined halftone type.

17. (Amended) The system as claimed in claim [9] 8, further comprising:

calibration means for performing a plurality of calibration operations, each calibration operation using a distinct media type and halftone type combination;

said calibration means generating a tone-reproduction curve for each media type and halftone type combination calibration;

said calibration means comparing the plurality of tone-reproduction curves to group tone-reproduction curves having similar characteristics;

said calibration means selecting a single tone-reproduction curve from a group of tone-reproduction curves having similar characteristics, each single tone-reproduction curve being the tone-reproduction curve associated with the media type and halftone type combinations that generated the tone-reproduction curve having similar characteristics;

said storage device storing selected and non-grouped tone-reproduction curves;